







With a 200-litre tank capacity, it allows for greater autonomy, reducing the need for frequent stops to recharge. In addition, the maximum air flow rate of 400 L/min ensures a constant and efficient air flow, ideal for pneumatic tools and other applications that require a continuous supply of compressed air. The 4 wheels make it easy to move and transport. With thermal protection to prevent damage from overheating. The non-return valve and safety valve ensure a safe operation. With an air filter that protects internal components and improves compressed air quality, reducing maintenance and increasing overall equipment effectiveness. The oil level sight glass allows the user to monitor the correct oil level, which is essential for the proper functioning and longevity of the compressor.

Key features

- > 200 litres capacity;
- > Maximum air flow rate of 400 L/min;
- > Belt drive transmission system 2800rpm (increased durability);
- > Oil level sight glass;
- > Prevents overheating;
- > Efficient energy consumption.





Specifications

Specifications	
Check valve	Yes
Dimensions	1375 x 440 x 855 mm
Engine oil	15W-40
IP code	IP44
Maximum flow rate	400 L/min
No-load Speed	2800 rpm
Oil crankcase capacity	1000 ml
Oil level sight glass	Yes
On/off switch	Yes
Operating pressure	10 bar / 145 psi
Packaging dimensions	1400 x 470 x 940 mm
Product weight	120 Kg
Rated power	4 cv / 3 kW
Rotation speed	950 rpm
Safety valve	Yes
Sound power level (LWA)	85 dB(A), k = 3
Tank capacity	200 L
Tank top outlet for fixed network connection	Yes
Thermal protection	Yes
Weight with packaging	136 Kg

December 14, 2025, 13:03h Page 1 of 1 VITO - Tools for the brave | Subject to correction or change without prior notice. vito-tools.com