







BELT-DRIVE COMPRESSOR 50L VICOC50

With a working pressure of 8 bar (115 psi) is the ideal choice for the most demanding jobs, anything from industrial use to work in repair shops and construction sites. With a 50-litre tank capacity, it allows for greater autonomy, reducing the need for frequent stops to recharge. In addition, the maximum air flow rate of 233 L/min ensures a constant and efficient air flow, ideal for pneumatic tools and other applications that require a continuous supply of compressed air. With an air filter and an IP20 rating, it provides basic protection for internal components and improves the quality of the compressed air, reducing maintenance and increasing overall equipment effectiveness in controlled environments.

Key features

- > 50 litres capacity;
- > Maximum air flow rate of 233 L/min;
- > Belt drive transmission system 1400rpm (increased durability);
- > Constant and efficient airflow;
- > Air filter;
- > IP20 rating, to carry out all tasks safely;
- > Greater power, durability, and less vibration.

Specifications

| Engine oil | 15W-40 |
|--|-----------------|
| Height | 690 mm |
| IP code | IP20 |
| Length | 940 mm |
| Maximum flow rate | 233 L/min |
| No-load Speed | 2850 rpm |
| Oil crankcase capacity | 326 ml |
| On/off switch | Yes |
| Operating pressure | 8 bar / 115 psi |
| Product weight | 51.086 kg |
| Rated power | 2,5 cv / 1,9 kW |
| Rotation speed | 1350 rpm |
| Safety valve | Yes |
| Sound power level (LWA) | 95 dB(A), k = 3 |
| Tank capacity | 50 L |
| Tank top outlet for fixed network connection | Yes |
| Thermal protection | Yes |
| Weight with packaging | 54.125 kg |
| Width | 380 mm |

Package Contents

| Included accessories: - Wheels | |
|--------------------------------|--|
| - Air filter. | |

Page 1 of 1 December 05, 2025, 18:11h vito-tools.com