



TWO-CYLINDER OIL COMPRESSOR 50LT 10 BAR 3.0HP VICODC50



This 50 L professional air compressor with a 3.0 hp (2.2 kW) oil-lubricated motor and dual-cylinder system delivers stable airflow for pneumatic tools used in workshops, maintenance, carpentry and construction. Operating at 10 bar, it supports demanding equipment such as impact wrenches, nailers, spray guns and blow guns. With a 334 L/min maximum airflow and 2850 rpm motor speed, it ensures consistent performance even under frequent cycles. The compressor is lubricated with 15W-40 oil, improving durability and thermal stability. It includes thermal protection, a safety valve, On/Off switch and top outlet for fixed-line connection. The 50 L tank ensures improved autonomy and reduced downtime.

Key features

- > 3.0 hp oil-lubricated motor with dual cylinder
- > 50 L tank for extended pressure stability
- > 10 bar operating pressure for demanding pneumatic tools
- > 334 L/min airflow for professional applications
- > 15W-40 lubrication for increased durability
- > Thermal protection and safety valve included
- > Top outlet for fixed-line setups
- > Ideal for workshop, painting and construction tasks



Specifications

Engine oil	15W-40
Maximum flow rate	334 L/min
Oil crankcase capacity	250 ml
On/off switch	Yes
Operating pressure	10 bar / 145 psi
Rotation speed	2850 rpm
Safety valve	Yes
Sound power level (LWA)	95 dB(A)
Tank capacity	50 L
Tank top outlet for fixed network connection	Yes
Thermal protection	Yes
IP code	IP20
Rated power	3,0 HP / 2,2 kW
Supply voltage	230V AC 50Hz