



SILENT OIL-FREE AIR COMPRESSOR 50L 8 BAR 2.0HP

VICSOS50A

The 50-litre tank combined with its characteristics, give it the capacity and versatility for domestic or professional use in the mechanical, chemical, pharmaceutical, decoration industry, among others. The heat dissipation fan and thermal protection ensure efficient protection preventing the motor from overheating. Supplied with rubber feet to protect surfaces from scratches and to stabilise and absorb any vibrations. The wheels provide the necessary mobility for transporting the compressor at work or projects at home.

Key features

- > Low-noise oil-free motor;
- > Pressure relief valve;
- > ON/OFF switch;
- > Thermal protection.



Specifications

Dimensions	680 x 380 x 625 mm																		
IP code	IP20																		
Low-noise, oil-free motor	Yes																		
Max. suction air rate	236 L/min																		
On/off switch	Yes																		
Operating pressure	8 bar / 115 psi																		
Output flow (0 Bar)	220 L/min																		
Output flow (4 Bar)	147 L/min																		
Output flow (6 Bar)	121 L/min																		
Output flow (7 Bar)	108 L/min																		
Packaging dimensions	mm																		
Product weight	28 kg																		
Rated power	2 cv / 1.5 kW																		
Rotation speed	2850 rpm																		
Sound power level (LWA)	87 dB(A)																		
Sound pressure level (LPA)	59.6 dB(A) (7m)																		
Supply voltage	230 V 50 Hz																		
Tank capacity	50 L																		
Thermal protection	Yes																		
Weight with packaging	kg																		

Variants

Reference	Dimensions	Ip Code	Low-Noise, Oil-Free Motor	Max. Suction Air Rate	On/Off Switch	Operating Pressure	Output Flow (0 Bar)	Output Flow (4 Bar)	Output Flow (6 Bar)	Output Flow (7 Bar)	Packaging Dimensions	Product Weight	Rated Power	Rotation Speed	Sound Power Level (Lwa)	Sound Pressure Level (Lpa)	Supply Voltage	Tank Capacity	Thermal Protection	Weight With Packaging
vicos50a	680 x 380 x 625 mm	ip20	yes	-	yes	8 bar / 115 psi	-	-	-	-	mm	28 kg	2 cv / 1.5 kw	2850 rpm	87 db(a)	-	-	50 l	yes	kg

VICS0550A	-	-	-	236 l/min	-	-	220 l/min	147 l/min	121 l/min	108 l/min	-	-	-	-	-	59.6 db(a) (7m)	230 v 50 hz	-	-	-
-----------	---	---	---	--------------	---	---	--------------	--------------	--------------	--------------	---	---	---	---	---	-----------------------	----------------	---	---	---