



## SUPER SILENT THREE-PHASE DIESEL GENERATOR 50kVA

### VIGD50ST

Super Silent Three-Phase Diesel Generator with a maximum power of 50kVA, combining resistance, stability, reliability and a low noise level. Suitable for power supply in emergencies, homes, industry, construction and commerce. It has an emergency power (STP) of 55kVA/44kW and 50kVA/40kW in continuous mode (PRP), with an output voltage of 230V AC 50Hz | 400V AC 50Hz. This model includes an intuitive controller with various functions to facilitate the operation and maintenance of the generator. It also comes equipped with an automatic voltage regulator (AVR) and an electric start control system. The canopy is made from sheet steel, insulated with anti-noise and anti-fire material, painted in epoxy polyester with anti-corrosion treatment. It has interior linings to absorb noise, which makes this model super silent and also allows air to flow through to cool down the engine. The chassis is designed to allow the generator to be moved by forklift and comes equipped with a 100L fuel tank. This generator can be connected to an ATS (Automatic Transfer Switch), so when there is a fault/disruption in the electricity supply, it automatically switches on the generator to supply power. The ATS board also switches off the generator once the power is restored.

#### Key features

- Continuous Power Mode 50kVA (PRP)
- Super Silent
- Intuitive controller for the operation and maintenance of the generator
- Automatic Voltage Regulator (AVR)
- Anti-noise and anti-fire canopy
- Chassis designed for the transport of the generator
- 100L Fuel Tank
- Allows connection to ATS

#### Specifications

Autonomy	<b>10 H</b>
Dimensions	<b>2270 x 1000 x 1300 mm</b>
Engine displacement	<b>3.707 L with turbo</b>
Fuel	<b>Diesel</b>
Output voltage	<b>230 V AC ~ 50 Hz 400 V AC ~ 50 Hz</b>
Power factor (cos Ø)	<b>0.8 cos Ø</b>
Prime Power (PRP)	<b>50 kVA / 40 kW</b>
Product weight	<b>1150 K</b>
Rated output current	<b>72 A</b>
Sound power level (LWA)	<b>67 dB(A), k = 7</b>
Standby power (STP)	<b>55 kVA / 44 kW</b>
Tank capacity	<b>100 L</b>