



DIESEL TILLER WITH DIRECT TRANSMISSION - 12HP

VIMEDTD12A

The VITO's robust and powerful tiller has been designed to work in a comfortable and agile way, achieving maximum quality in the soil. Its 456cc diesel engine with an output power of 12hp/8.9kW is fitted with a 2-speed gearbox (2 forward + 1 reverse) for maximum performance. The appliance includes a double furrow opener, 360mm diameter tines. It has a working width of 1450mm being suitable medium or large-sized terrains. This environmental friendly and Euro V compliant appliance is ideal for those looking for quality and performance.

Key features

- > Electric start;
- > Triple filtering;
- > Oil level sensor;
- > Protection grille with light.



Specifications

Battery for electric start	Yes
Engine	4-ST combustion
Engine displacement	456 cc
Engine oil	15W40
Engine oil crankcase	1,65 L
Fuel	Diesel
Fuel tank capacity	5,5 L
Gear oil	2,5L
Gearbox oil	80W90
Height	860 mm
Length	1010 mm
Product weight	178.5 kg
Rated power	12 cv / 8.9 kW
Rotation speed	3600 rpm
Sound power level (LWA)	98dB
Speeds	2 forward + 1 reverse
Tine diameter	360 mm
Transmission	Direct
Weight with packaging	190.000 kg
Width	640 mm
Working width	1450 mm

Variants																					
Reference	Battery For Electric Start	Engine	Engine Displacement	Engine Oil	Engine Oil Crankcase	Fuel	Fuel Tank Capacity	Gear Oil	Gearbox Oil	Height	Length	Product Weight	Rated Power	Rotation Speed	Sound Power Level (Lwa)	Speeds	Tine Diameter	Transmission	Weight With Packaging	Width	Working Width

VIMEDTD12A	yes	4-st combustion	456 cc	15w40	1,65 l	diesel	5,5 l	2,5l	80w90	860 mm	1010 mm	178.5 kg	12 cv / 8.9 kw	3600 rpm	98db	2 forward + 1 reverse	360 mm	direct	190.000 kg	640 mm	1450 mm
VIMEDTD12A.M	yes	4-st combustion	456 cc	15w40	1,65 l	diesel	5,5 l	2,5l	80w90	860 mm	1010 mm	178.5 kg	12 cv / 8.9 kw	3600 rpm	98db	2 forward + 1 reverse	360 mm	direct	190.000 kg	640 mm	1450 mm