



## 4D 16-LINE LASER LEVEL 60M VINL4D16L60



This tool features a projection of green horizontal, vertical, and cross lines at 360°, ensuring visibility even in challenging environments. Suitable for measuring and alignment applications, it can be used in construction, installation, and finishing work on materials such as drywall. With a range of up to 60 meters and an accuracy of ±0.2 mm/m, this level is ideal for professional alignment tasks. Additionally, it can be used with the receiver (VIRCNL) to achieve a range of up to 140 meters. Thanks to the automatic pendulum leveling system, the equipment is quick and easy to use. It is also equipped with a rotating base with bubble and micro-adjustment, ensuring stable and controlled positioning. In addition, it includes a remote control, adding versatility by allowing operation from a distance. The IP54 protection rating makes it suitable for demanding environments, offering resistance to dust and water splashes.



### Key features

- > Accuracy of ±0.2 mm/m, ensuring precise leveling;
- > Versatility ensured by the 60-meter range;
- > Use with receiver allows a range of up to 140 meters;
- > Projection of green cross lines that facilitate alignment;
- > Suitable for construction, installation, and drywall finishing;
- > Automatic pendulum leveling for faster operation;
- > Convenience thanks to the integrated remote control;
- > Rotating base with bubble and micro-adjustment, promoting level stability;
- > IP54 protection rating, resistant to dust and water splashes.

### Specifications

Automatic self-leveling	<b>Yes</b>
Holder	<b>Yes</b>
Integrated 1/4" locking thread	<b>Yes</b>
Laser line width	<b>100 lux, 2 mm/5 m</b>
Laser output power	<b>Class 2 &lt; 1mW</b>
Laser wavelength	<b>520 nm</b>
Leveling range	<b>3°</b>
Leveling unit locking	<b>Yes</b>
Line projection	<b>Yes</b>
Measure time	<b>±4s</b>
Measurement accuracy	<b>± 0,2 mm/m</b>
Power cord	<b>Yes</b>
Working Range	<b>60m / 140m (with receiver)</b>
Autonomy	<b>&gt; 6 h</b>
Battery	<b>7.4V, 2600mAh x2</b>
Dimensions	<b>154 x 129 x 90 mm (Laser level only)</b>
Product weight	<b>753g (Laser level only)</b>
IP code	<b>IP54</b>
Operating temperature	<b>10 - 50° C</b>

### Package Contents

- BMC case
- 2 x 7.4V 2,600 mAh batteries
- Charger USB - C
- Magnetic mount
- Rotating mount
- Height-adjustable base
- Upper clamp mount
- Remote control
- 2 x AAA batteries
- Green target plate for laser level
- Instruction manual

Operating radius	<b>30m / 70m (with receiver)</b>
Voltage	<b>7.4V</b>