



5-LINE LASER LEVEL 60M VINLTT5L60

With a reinforced structure, this equipment is suitable for measurement and alignment applications in construction, installation, and finishing work on materials such as drywall. Its drop-resistant design up to 2 meters enhances durability and extends its service life. The 5-line TT laser ensures professional performance, featuring an accuracy of ± 0.22 mm/m. Additionally, it includes a self-leveling system that ensures automatic position correction. With projection of green horizontal, vertical, and cross lines and a range of 60 m, it can be used with the receiver (VIRCNL) to achieve a range of up to 140 meters. The level is also equipped with a remote control for added convenience and a rotating base with bubble and micro-adjustment for stable and controlled positioning. The IP54 protection rating makes it suitable for demanding environments, offering resistance to dust and water splashes.

Key features

- > Accuracy of ± 0.22 mm/m, ensuring precise leveling;
- > Versatility ensured by the 60-meter range;
- > Use with receiver allows a range of up to 140 meters;
- > Drop-resistant design up to 2 meters;
- > Suitable for construction, installation, and drywall finishing;
- > Automatic system to ensure correct leveling;
- > Robust structure for enhanced resistance and durability;
- > Projection of green cross lines that facilitate alignment;
- > Convenience thanks to the integrated remote control;
- > Rotating base with bubble and micro-adjustment, promoting level stability;
- > IP54 protection rating, resistant to dust and water splashes.



Specifications

Automatic self-levelling	Yes
Holder	Yes
Integrated 1/4" locking thread	Yes
Laser line width	100 lux, 2,5 mm/7 m
Laser output power	Classe 2 < 1 mW
Laser wavelength	520 nm
Leveling range	3°
Leveling unit locking	Yes
Line projection	Yes
Measure time	± 4s
Measurement accuracy	± 0,22 mm/m
Power cord	Yes
Working Range	60m / 140m (with receiver)
Autonomy	> 4 h
Battery	3.7V, 4000mAh x2
Dimensions	140 x 140 x 200 mm (Laser level only)
Product weight	1100g (Laser level only)
IP code	IP54
Operating temperature	10 - 50° C

Package Contents

- BMC case
- 2 x 3.7V 4,000 mAh batteries
- USB-A Charger
- USB-C cable
- 3/8"M to 1/4"F adapter
- Green target plate for laser level
- Green glasses
- Instruction manual.

Operating radius	30m / 70m (with receiver)
Voltage	3,7V