



Powered by  
**Kawasaki**

## PROFESSIONAL BRUSHCUTTER KWK 45CC - 1,9HP VIRK45

Equipped with a Kawasaki® engine, this brushcutter is designed for intensive, long-term cleaning work in green areas, where the durability and resistance of the equipment are crucial. As such, it is ideal for cutting and trimming dense vegetation in professional contexts that require consistent performance over time. This engine stands out for its high mechanical reliability, allowing you to maintain a constant working pace, which reduces downtime and increases productivity in lengthy tasks. Furthermore, the spark arrestor included in the machine enhances safety during use, especially in more sensitive agricultural or forestry environments. Designed for user comfort, the brushcutter features an EasyStart system, which makes start-up easier, and an anti-vibration system, which helps reduce fatigue during continuous use. In addition, the included support harness promotes ergonomics and weight distribution, making work more comfortable and controlled, especially during extended periods of time.



### Key features

- > Kawasaki® engine renowned for its reliability and durability;
- > Suitable for demanding jobs and prolonged use;
- > Consistent performance in dense vegetation;
- > Spark arrestor, ensuring greater safety;
- > Easy start-up thanks to the EasyStart system;
- > Reduced fatigue thanks to the anti-vibration system;
- > Support harness included for added comfort.

### Specifications

|                                       |                              |
|---------------------------------------|------------------------------|
| Cutting blade width                   | <b>255 mm</b>                |
| Engine                                | <b>2-Stroke combustion</b>   |
| Engine displacement                   | <b>45,4 cc</b>               |
| Fuel                                  | <b>Mixture - 1: 40 ratio</b> |
| Fuel tank capacity                    | <b>0,9 L</b>                 |
| Idle speed                            | <b>3000 ± 400 rpm</b>        |
| Maximum rotation speed (engine)       | <b>10000 / 10500 rpm</b>     |
| Maximum rotation speed (shaft)        | <b>7750 / 8150 rpm</b>       |
| Nylon line diameter                   | <b>2.4 mm</b>                |
| Shaft tube diameter                   | <b>28 mm</b>                 |
| Sound power level (LWA)               | <b>113dB</b>                 |
| Vibration level with auxiliary handle | <b>3.39 ± 1.5</b>            |
| Vibration level with main handle      | <b>3.05 ± 1.5</b>            |
| Engine brand                          | <b>Kawasaki</b>              |
| Frame                                 | <b>Aluminium</b>             |
| Rated power                           | <b>1,9 cv / 1,42 kW</b>      |

### Variants

#### Reference

**VIRK45**

VIRK45