



## Specifications

(Bevel) Max. width x cutting depth 45°/0°	<b>87 mm</b>
(Bevel) Max. width x cutting depth 45°/45°	<b>60 mm</b>
(Miter) Max. width x cutting depth 0°/0°	<b>87 mm</b>
(Miter) Max. width x cutting depth 0°/45°	<b>60 mm</b>
Assembly	<b>Not Assembled</b>
Blade diameter	<b>315 mm</b>
Blade hole diameter	<b>30 mm</b>
Cutting angle (bevel)	<b>0° / 45°</b>
Cutting angle (miter)	<b>- 60° / 0° / + 60°</b>
Disc thickness	<b>3 mm</b>
Engine	<b>Induction</b>
Height	<b>450 mm</b>
Length	<b>870 mm</b>
Miter gauge	<b>Yes</b>
No-load Speed	<b>2950 rpm</b>
Number of teeth on the blade	<b>40 dentes</b>
Packaging dimensions	<b>870 x 590 x 445 mm</b>
Parallel guide	<b>Yes</b>
Product weight	<b>52.481 kg</b>
Rated power	<b>2000 W</b>
Sound power level (LWA)	<b>109 dB(A), k = 3</b>
Weight with packaging	<b>55.000 kg</b>
Wheels and carrying handles	<b>Yes</b>
Width	<b>585 mm</b>