



## SDS-PLUS DRILL BIT PRO

### VISDSP10160

The VITO SDS-Plus Pro drill bit delivers maximum efficiency and durability for demanding drilling tasks in stone and concrete. Equipped with 4 embedded cutting edges and embedded brazing technology, it ensures fast dust removal, reduced wear and higher drilling speed. With PGM certification, it meets the highest quality and precision standards for consistent and safe performance. Withstands temperatures up to 600 °C, maintaining excellent performance even under demanding use. Ideal for professional applications with SDS-Plus rotary hammers, ensuring clean, fast and reliable results on every job.



#### Key features

- > 4 embedded cutting edges for fast, precise drilling.
- > PGM certification ensures quality and accuracy.
- > Heat resistance up to 600 °C for superior durability.
- > Embedded brazing prevents tip detachment.
- > Fast dust removal and reduced wear.
- > Ideal for stone, concrete and reinforced concrete.
- > Compatible with SDS-Plus rotary hammers.
- > Professional performance with excellent stability and precision.

#### Specifications

Diameter	<b>10 mm</b>
Length	<b>160 mm</b>
Size	<b>10 mm x 160 mm</b>
Suitable for	<b>Stone and concrete</b>

#### Variants

Reference	Size
<b>VISDSP10160</b>	10 mm x 160 mm
<b>VISDSP10210</b>	10 mm x 210 mm
<b>VISDSP10260</b>	10 mm x 260 mm
<b>VISDSP10310</b>	10 mm x 310 mm
<b>VISDSP121000</b>	12 mm x 1000 mm
<b>VISDSP12160</b>	12 mm x 160 mm
<b>VISDSP12210</b>	12 mm x 210 mm
<b>VISDSP12260</b>	12 mm x 260 mm
<b>VISDSP12600</b>	12 mm x 600 mm
<b>VISDSP14160</b>	14 mm x 160 mm
<b>VISDSP14210</b>	14 mm x 210 mm
<b>VISDSP14260</b>	14 mm x 260 mm
<b>VISDSP16210</b>	16 mm x 210 mm
<b>VISDSP16260</b>	16 mm x 260 mm

<b>VISDSP16310</b>	16 mm x 310 mm
<b>VISDSP16350</b>	16 mm x 350 mm
<b>VISDSP16450</b>	16 mm x 450 mm
<b>VISDSP18260</b>	18 mm x 260 mm
<b>VISDSP18450</b>	18 mm x 450 mm
<b>VISDSP20260</b>	20 mm x 260 mm
<b>VISDSP20450</b>	20 mm x 450 mm
<b>VISDSP22260</b>	22 mm x 260 mm
<b>VISDSP22450</b>	22 mm x 450 mm
<b>VISDSP24450</b>	24 mm x 450 mm
<b>VISDSP25450</b>	25 mm x 450 mm
<b>VISDSP5110</b>	5 mm x 110 mm
<b>VISDSP5160</b>	5 mm x 160 mm
<b>VISDSP6110</b>	6 mm x 110 mm
<b>VISDSP6160</b>	6 mm x 160 mm
<b>VISDSP6210</b>	6 mm x 210 mm
<b>VISDSP6260</b>	6 mm x 260 mm
<b>VISDSP8110</b>	8 mm x 110 mm
<b>VISDSP8160</b>	8 mm x 160 mm
<b>VISDSP8210</b>	8 mm x 210 mm
<b>VISDSP8260</b>	8 mm x 260 mm